ISSN: 3139-0862

A Survey of AI-Driven Digital Wellbeing Systems: Smartphone Behaviour Analysis, Personalization, and Adaptive Interventions

Manasvi Patil[1], Pranav Desai[2], Aniket Malik[3], Adinath Kashte[4], Prof. Nilima Matre[5]
[1, 2, 3, 4]Students, [5]Assistant Professor, Department of Computer Engineering,
Watumull Institute of Engineering & Technology, Ulhasnagar, University of Mumbai, Maharashtra, India

Abstract

Mobile smartphones now serve as essential tools across education, professional duties, personal communication, and daily administration. Despite their utility, habituated checking behaviors, prolonged sessions, and poorly timed notifications frequently disrupt personal productivity and cognitive focus. Standard operating system utilities supply static screen time metrics and app limits, yet struggle to account for user intention or mental context. Recent research in human-computer interaction and mobile computing explores personalized, machine learning-driven interventions designed to adapt to individual usage routines. This survey reviews contemporary developments across five key domains: device telemetry extraction, self-regulation interfaces, micro-nudging mechanics, context-aware notification scheduling, and human-centred artificial intelligence architectures. We synthesize existing empirical studies across performance metrics, data collection techniques, personalization depth, and methodological constraints. The findings indicate that raw usage duration is a weak signal for psychological strain, while intervention success hinges on environmental context and individual motivation. Key challenges remain regarding data privacy, model interpretability, and long-term user agency. Finally, we present a modular architectural direction combining local telemetry processing, explainable baseline modeling, uncertainty estimation, and user-governed intervention controls.

Keywords— Digital Wellbeing, Mobile Telemetry, Behaviour Analysis, Personalization, Digital Nudges, Context-Aware Systems, Human-Centred AI.

I. INTRODUCTION

Smartphones have evolved into central hubs for personal and professional life. They handle navigation, academic research, real-time messaging, remote collaboration, and leisure activities within a single, highly accessible interface. Because modern mobile hardware accommodates such diverse tasks, measuring screen engagement purely by total duration yields limited insight into user focus or psychological state.

A ninety-minute mobile session may represent deep academic reading, critical remote coordination, or aimless social media scrolling driven by boredom or anxiety. As a result, digital wellbeing cannot be treated simply as a mandate to cut screen time. Instead, it involves aligning phone usage with immediate intent, supporting sleep hygiene, preserving attention spans, and minimizing cognitive friction.

Commercial mobile platforms offer built-in self-management tools, including daily usage charts, application timers, and focus modes. While these utilities help raise basic awareness, their effectiveness relies heavily on a user's proactive effort and self-control. Static friction mechanics often fail when users encounter high stress or routine disruptions.

Empirical research into persuasive design shows that universal rules rarely hold across diverse user cohorts. Interventions that help one user manage screen habits may cause frustration or prompt workaround behaviors in another. Furthermore, recent reviews point out that AI-driven interventions remain fragmented across isolated prototype applications without standard design rules.

To organize current developments in this field, this survey frames existing research around five primary research questions:

RQ1: What behavioral signals can be reliably collected using native mobile telemetry APIs without violating user privacy?

RQ2: How effectively do current self-management tools
support long-term self-regulation and intentional phone use?

RQ3: What does empirical evidence indicate regarding digital nudges, notification timing, and intervention delivery?

RQ4: How can machine learning models be integrated into mobile systems while maintaining transparency and user trust?

RQ5: What technical, methodological, and ethical gaps persist in contemporary digital wellbeing literature?

II. SURVEY SCOPE AND METHODOLOGY

This survey uses a narrative review approach to synthesize findings from human-computer interaction (HCI), mobile ubiquitous computing, behavioral psychology, and applied machine learning. The primary reference corpus comprises peer-reviewed empirical studies, systematic reviews, developer platform documentations (such as Android system frameworks), and open-source machine learning repositories.

Literature was selected based on its direct relevance to smartphone telemetry monitoring, persuasive micro-nudging, adaptive notification batching, context sensing, or ethical AI framework design. Operating system documentation is referenced strictly to clarify platform capabilities and API

ISSN: 3139-0862

security models, rather than as evidence of intervention efficacy.




Fig. 1. Systematic Review Method & Synthesis Workflow

Because this paper provides a targeted synthesis rather than a formal PRISMA meta-analysis, it does not detail exact search string counts or PRISMA flow diagrams. Future systematic reviews can build on this narrative foundation by executing structured database queries across IEEE Xplore, ACM Digital Library, and PubMed with explicit risk-of-bias tools.

III. MONITORING & SELF-MANAGEMENT

A. Mobile Telemetry APIs: Modern mobile operating systems expose dedicated interfaces to track application usage events under user permission. On Android, the `UsageStatsManager` and `UsageEvents` APIs grant access to application launch counts, foreground duration, notification dismissals, and device unlock timestamps [1], [2]. When configured appropriately, these system logs yield continuous time-series data reflecting device interaction patterns.

B. However, raw event logs fail to capture user context or mental state. Timestamped records cannot clarify whether a rapid sequence of app switches stems from productive multitasking, urgent communication, or restless procrastination. Designers must treat raw system metrics as low-level behavioral proxies rather than direct measures of focus or stress.

C. Dashboard Tools: Self-management utilities map raw usage event streams into visual dashboards, session limit alerts, grayscale modes, and intentional launch delays. Lee et al. developed the MindsCare platform to help users regulate phone habits, evaluating the tool with 342 adults over a 13-week field trial [5]. Their results indicated that structured reflection tools can lower self-reported compulsive usage. However, findings from specific user groups or intervention periods cannot automatically be generalized across all demographics or workplace environments.

IV. LITERATURE SYNTHESIS

A. Digital Nudges and Interventions: Digital nudging adjusts interface choice architecture—using visual cues, micro-boundaries, or brief delays—to encourage intentional phone use without restricting feature access [3]. Controlled trials evaluating micro-boundaries show that adding slight interface friction can interrupt habituated checking routines [6].

Yet intervention effects vary based on design and delivery mechanism. Ohme et al. evaluated a preregistered intervention where participants disabled all non-essential smartphone notifications [7]. Contrary to expectations, the trial observed no statistically significant decrease in total daily screen time or unlock frequency. This demonstrates that suppressing notifications alone may prompt compensatory checking, highlighting the need for context-sensitive delivery timing.

In another study, Vu and Tagliabue examined active night-time nudges aimed at reducing late-night phone engagement to improve sleep hygiene [8]. While initial trends showed reduced late-night usage, the study's sample size (N = 17) and 7-day duration limit broad generalizations. These findings underline that digital nudges must be evaluated against clear baseline controls over extended periods.




Fig. 2. Categorization of Smartphone Nudge Architectures

B. Personalization and Individual Variance: Personalization engines customize intervention timing, tone, and delivery modes based on user goals, historical usage trends, and past responses. In a study on mobile notification adaptation for behavior change, Jankovič et al. observed substantial variance in how individual participants reacted to identical notification triggers [9]. Their findings demonstrate that personalized intervention logic must be empirically tested across distinct user subgroups rather than treated as a guaranteed performance boost over static rules.

Establishing personal baselines represents a promising alternative to fixed screen-time caps. Instead of enforcing global limits, an adaptive system evaluates current activity against a user's typical schedule. However, baseline algorithms can misinterpret lifestyle shifts—such as vacations, exam periods, illness, or job changes. Wellbeing platforms must accommodate missing telemetry, filter short-term outliers, and allow manual

ISSN: 3139-0862

overrides when daily routines change.

C. AI and Human-Centred Principles: Machine learning algorithms excel at pattern classification, time-series forecasting, and anomaly detection [4]. However, high offline predictive accuracy does not guarantee improved user wellbeing. Classifiers trained on proxy labels may simply memorize hardcoded duration limits rather than underlying behavioral patterns.

To address these concerns, recent research emphasizes human-centred AI principles. In a systematic review of 240 multidisciplinary studies, Shin proposed a human-centred framework mapping relationships between system architecture, user internal state, and behavioral outcomes [10]. Similarly, Scibetta et al. synthesized AI-driven wellbeing literature into a design framework prioritizing privacy, transparency, and user agency [11]. Both works argue that AI models should support user decision-making rather than act as opaque, automated decision-makers.

TABLE I: COMPARATIVE SUMMARY OF REVIEWED LITERATURE

Study / Source	Focus & Evidence Type	Core Findings & Contributions	Methodological Limitations
Android APIs [1], [2]	Technical Documentation	Defines permissioned native APIs for tracking usage events	Event logging lacks psychological state or intent indicators
Fogg [3]	Theoretical Framework	Establishes core principles of persuasive technological design	Broad theoretical model lacking mobile-specific validation
Pedregosa et al. [4]	Software Tooling	Provides open-source Python tools for predictive modeling	Algorithmic performance does not guarantee user wellbeing
Lee et al. [5]	Empirical Field Trial (N=342)	Evaluated MindsCare platform over 13-week study period	Outcomes tied to specific app, cohort, and trial duration
RCT Study [6]	Randomized Controlled Trial	Demonstrated that nudge mechanisms reduce excess screen usage	Efficacy depends heavily on delivery context and user motivation
Ohme et al. [7]	Preregistered Evaluation	Tested complete notification disabling across mobile users	Single-strategy intervention failed to reduce overall screen time
Vu & Tagliabue [8]	Exploratory Study (N=17)	Investigated active night nudges and sleep quality impacts	Small cohort and 7-day evaluation restrict generalization
Jankovič et al. [9]	Behavioral Field Study	Identified individual variance in responses to adaptive nudges	Personalization rules must be validated per user subgroup
Shin [10]	Systematic Review (N=240)	Synthesized human-centred AI design framework for wellbeing	High-level framework requires direct empirical validation
Scibetta et al. [11]	Systematic Framework	Structured core design dimensions for intelligent wellbeing tools	Conceptual design principles require empirical field testing

V. RESEARCH GAPS & CHALLENGES

A. Construct Validity: Modern mobile operating systems track low-level usage metrics, such as session lengths, app launch counts, unlock frequencies, and notification timestamps. While these indicators generate detailed temporal logs, they remain imperfect proxies for cognitive focus, emotional fatigue, or personal productivity. Future work must bridge raw device telemetry with validated self-reports (such as Ecological Momentary Assessments) while enforcing strict data minimization to prevent intrusive tracking.

B. Label Quality and Model Interpretability: Automated behavioral labels such as 'focused work,' 'distracted usage,' or 'compulsive checking' require explicit operational definitions. If machine learning classifiers rely on fixed screen-time thresholds for training labels, they risk reproducing arbitrary hardcoded rules in their outputs. Researchers should document dataset annotation protocols, report inter-annotator agreement metrics, communicate model uncertainty, and avoid framing computational outputs as clinical assessments.

C. Baseline Adaptation to Concept Drift: Personalized baselines must adjust to routine lifestyle changes without overreacting to short-term disruptions (such as travel or exam weeks). Future studies should benchmark fixed thresholds against rolling statistical averages and adaptive concept-drift algorithms. Evaluators must report cold-start performance, missing data handling, cross-device stability, and whether personalized models systematically outperform simple non-personalized baselines.

D. User Autonomy and Alert Fatigue: Higher notification frequencies do not ensure better habit management. Frequent prompts can trigger notification fatigue, while rigid application blocks may frustrate users and reduce perceived autonomy. Empirical studies must evaluate user acceptance rates, prompt dismissals, perceived control, goal attainment, and potential side effects. Users should retain full control to pause, adjust, or override intervention mechanisms.

ISSN: 3139-0862

TABLE II: CONSOLIDATED RESEARCH GAPS & PROPOSED STRATEGIES

Gap Domain	System Design Impact	Recommended Future Evaluation Strategy
Construct Validity	Raw screen duration fails to reflect psychological wellbeing	Pair usage telemetry with validated Ecological Momentary Assessments
Label Quality & XAI	Opaque or rule-derived ML labels misinform users	Document annotation protocols, report uncertainty, and test user comprehension
Concept Drift	Static baselines misinterpret routine lifestyle shifts (exams, travel)	Benchmark rolling statistical baselines against adaptive drift models
User Autonomy	Intrusive prompts trigger notification fatigue and frustration	Measure dismissal rates, perceived agency scores, and long-term goal alignment
Data Privacy	Granular interaction logs expose sensitive user routines	Audit local on-device processing, encryption standards, and deletion controls
Reproducibility	Interventions fail to generalize across diverse user populations	Publish open datasets, model split protocols, and demographic audits

VI. CONCEPTUAL ARCHITECTURE

Based on our review of existing systems, future digital wellbeing platforms should operate as transparent, multi-stage processing pipelines rather than opaque scoring algorithms. System architecture should prioritize local data processing, simple interpretable models, clear user controls, and continuous outcome assessment.




Fig. 3. End-to-End System Pipeline Architecture

VII. IMPLICATIONS FOR EVALUATION

Evaluating adaptive digital wellbeing platforms requires a comprehensive protocol spanning four distinct dimensions: (1) System Verification; (2) Predictive Model Metrics (MAE/RMSE for duration forecasting, F1 - score for behavior detection); (3) User Usability & Agency; and (4) Longitudinal Habit Tracking.

VIII. LIMITATIONS OF THIS SURVEY

This paper presents a targeted narrative survey rather than an exhaustive PRISMA-compliant systematic review. It does not report formal search queries, multi-database duplicate counts, or meta-analytic effect sizes. While selected studies cover core themes in telemetry tracking, digital nudging, notification adaptation, and human-centred AI, relevant literature may exist outside our source selection. Furthermore, differences in study populations, intervention designs, evaluation periods, and performance metrics prevent direct statistical meta-analysis. As a result, this paper provides a structured thematic synthesis to inform future research rather than a definitive ranking ofdigital wellbeing platforms.

IX. CONCLUSION

This survey reviewed contemporary developments in smartphone usage logging, digital self-management tools, persuasive micro-nudges, adaptive notification scheduling, and human-centred AI frameworks. The literature demonstrates that while native mobile APIs enable reliable telemetry extraction, raw screen time serves as an incomplete metric for psychological wellbeing. Intervention outcomes depend heavily on personal context, and integrating AI requires careful attention to data privacy, model interpretability, construct validity, and user autonomy. The main research opportunity lies in bridging raw behavioral telemetry with validated user outcomes through transparent, context-aware systems evaluated in long-term field studies. Future platforms should prioritize explainable baselines, non-intrusive nudges, and strong privacy safeguards—ensuring technology supports human goals without making unverified clinical claims.

CONFLICT OF INTEREST

The authors declare that there is no conflict of interest regarding the publication ofthis paper.

ACKNOWLEDGEMENT

The authors express sincere gratitude to the faculty and staff of the Department of Computer Engineering at Watumull Institute of Engineering & Technology, Mumbai, for continuous academic guidance, technical encouragement, and institutional support throughout this research survey.

REFERENCES

1. Android Developers, "UsageStatsManager, Android API Reference," https://developer.android.com/reference/android/app/usage/UsageStatsManager
2. Android Developers, "UsageEvents, Android API Reference," https://developer.android.com/reference/android/app/usage/UsageEvents
3. B. J. Fogg, *Persuasive Technology: Using Computers to Change What We Think and Do*, Morgan Kaufmann, 2003.
4. F. Pedregosa et al., "Scikit-learn: Machine Learning in

ISSN: 3139-0862

Python," *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.

5. S. J. Lee, M. J. Choi, S. H. Yu, H. Kim, S. J. Park, and I. Y. Choi, "Development and evaluation ofsmartphone usage management system for preventing problematic smartphone use," *Digital Health*, vol. 8, pp. 1–14, 2022.

6. "A Nudge-Based Intervention to Reduce Problematic Smartphone Use: Randomised Controlled Trial," *PLOS ONE*, 2022.

7. J. Ohme, L. Araujo, T. E. De Leyn, and L. De Marez, "Beyond the Buzz: Investigating the Effects ofa Notification-Disabling Intervention on Smartphone Behavior and Digital Well-Being," *Media Psychology*, vol. 27, no. 4, pp. 512–535, 2024.

8. T. H. Vu and M. Tagliabue, "Active nudging towards digital well-being: reducing excessive screen time on mobile phones and potential improvement for sleep quality," *Frontiers in Psychiatry*, vol. 16, p. 1602997, 2025.

9. A. Jankovič, T. Kolenik, and V. Pejović, "Can Personalization Persuade? Study of Notification Adaptation in Mobile Behavior Change Intervention Application," *Behavioral Sciences*, vol. 12, no. 5, p. 116, 2022.

10. Y. Shin, "Toward Human-Centered Artificial Intelligence for Users' Digital Well-Being: Systematic Review, Synthesis, and Future Directions," *JMIR Human Factors*, vol. 12, p. e69533, 2025.

11. L. Scibetta, M. Pellegrino, A. Monge Roffarello, and L. De Russis, "Intelligent support for digital wellbeing: A design framework through a systematic literature review," *International Journal ofHuman-Computer Studies*, vol. 205, p. 103653, 2025.